

## HRT-BF(441/2)-758N-- Cavity Bandpass Filter

Electrical Specifications			Product Picture	
Parameter	Unit	Specification		
Center Frequency:	MHz	441		
Bandwidth:	MHz	2		
Insertion Loss:	dB	Max	1.25@441Mhz	
Ripple :	dB	Max	TBD	
Return Loss:	dB	Min	15	
Group delay:	ns	Max	TBD	
Power Handling:	W	Max	25W	
Rejection:	≥40dB@417MHz,451MHz			
Mechanical Specifications		Environmental Specification		
Parameter	Specification	Parameter	Specification	
Input Connectors:	N-Female (50Ω)	Operating Temp.	-40°C to +70°C	
Output Connectors:	N-Female (50Ω)	Storage Temp.	-55°C to +85°C	
Size Tolerance:	As Below(±0.3mm)	Environment Class:	TBD	
ROHS:	Yes	Altitude:	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment)(Optional)	
Material:	Aluminum			
Weight(Kg):	TBD	Humidity:	95%RH at 40°C	
Suface Finish:	Black	Shock:	20G for 11msec half sine wave,3 axis both directions	
Note:				

### Configuration:



