

## HRT-BF(610/20)-753D-- Cavity Bandpass Filter

Electrical Specifications			Product Picture	
Parameter	Unit	Specification		
Center Frequency(F0):	MHz	610		
Bandwidth:	MHz	20(600-620)		
Insertion Loss:	dB	Max	1.5@F0	
Ripple:	dB	Max	TBD	
Return Loss:	dB	Min	14	
Group delay:	ns	Max	TBD	
Power Handling:	W	Max	1W	
Rejection:	≥60dB@598MHz,622MHz			
Mechanical Specifications		Environmental Specification		
Parameter	Specification	Parameter	Specification	
Input Connectors:	Din-Female (50Ω)	Operating Temp.	-40°C to +70°C	
Output Connectors:	Din-Female (50Ω)	Storage Temp.	-55°C to +95°C	
Size Tolerance:	As Below(±0.3mm)	Environment Class:	TBD	
ROHS:	Yes	Altitude:	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment)(Optional)	
Material:	Aluminum			
Weight(Kg):	TBD	Humidity:	95%RH at 40°C	
Surface Finish:	Black	Shock:	20G for 11msec half sine wave,3 axis both directions	
Note:				

### Configuration:



