



Cavity Filter

- ◆ High Rejection
- ◆ Low Insertion Loss
- ◆ Miniaturization
- ◆ Excellent Reliability
- ◆ Customization available

The HRT-BF(1621/10.5)-265S is a cavity band pass filter. The pass band is 1616-1626.5MHz. It has excellent rejection $\geq 40\text{dB}$ @ 1563.42-1587.42MHz. It has a maximum insertion loss of 1.0dB. The filter has SMA-Female connectors.



Electrical Specifications

Parameters	Units		Specifications
Center Frequency(CF)	MHz		1621
Pass Band Frequency	MHz		1616-1626.5
Insertion Loss	dB	Max	1.0
Pass Band Flatness	dB	Max	TBD
Return Loss	dB	Min	15
Group Delay Variation	ns	Max	TBD
Phase Matching	deg	Max	TBD
Rejection	$\geq 40\text{dB}$ @ 1563.42-1587.42MHz		
Power Handling	20W cw max		

50 ohms Coaxial Cavity Band Pass Filter

SN:2490-220208 Version: A0

Mechanical Specifications		Environmental Specification	
Parameter	Specification	Parameter	Specification
Input Connectors	SMA-Female (50Ω)	Operating Temp.	-40°C to +70°C
Output Connectors	SMA-Female (50Ω)	Storage Temp.	-55°C to +85°C
ROHS	Yes	Environment Class	TBD
Material	Aluminum (6061)	Altitude	30,000 ft.
Weight(Kg)	0.18		(Epoxy Sealed Controlled environment)
Surface Finish	Black Painted	Humidity	95%RH at 40°C
Shock	20G for 11msec half sine wave,3 axis both directions		
Note			

Outline Drawing:

All Dimensions in mm (inches)
 Outline Tolerances $\pm 0.3(0.012)$



